



INDUSTRIAL
FLOW
SOLUTIONS™

TECHNICAL DATA

BJM Pumps® JX15HSSF

Dwg:

DS-C09-007

Rev:

1

Date:

9/8/2025

GENERAL DATA

APPROVALS:	CSA APPROVAL (AVAILABLE UPON REQUEST)	
MAX. FLOW:	128 GPM (484.5 LPM)	
MAX. HEAD:	64' (19.5m)	
MAX. SUBMERSION DEPTH:	65' (20 m) or limited to length of power cord, Consult factory for deeper depths	
PUMP TYPE:	DEWATERING, SIDE DISCHARGE, HIGH TEMP	
MINIMUM SUBMERSION DEPTH FOR CONT. DUTY ³ :	9.5" (241.3 mm)	
PUMP DOWN WATER LEVEL:	5.25" (133.35 mm)	
SOLID SIZE:	0.19" (4.7 mm)	
STRAINER OPENING:	0.25" (6.3 mm)	
IMPELLER DIAMETER:	5.04" (128 mm)	
DISCHARGE SIZE:	2" NPT-MALE	
SLIDE RAIL SYSTEM	2" STAINLESS STEEL	
PUMP WEIGHT (without cable):	57 lbs (25.9 kg)	
SHIPPING WEIGHT:	66 lbs (29.9 kg)	

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR CASING	316 SS
IMPELLER & VOLUTE	316 SS
STRAINER	316 SS
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
BEARING, OIL LUBRICATED, UPPER:	6203
BEARING, OIL LUBRICATED, LOWER:	6304

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	2, SUBMERSIBLE OIL FILLED, (CONTINUOUS DUTY ³)			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	R, 428°F (220°C)			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 3PH - 60Hz ¹	208V	230V	460V	575V
CURRENT F.L.A.	6.3	6	3	2.3
LOCKED ROTOR CURRENT (LRA)	44.6	44	22	15.5
STANDARD POWER CABLE: GAGE-LENGTH	AWG 16/4, 33' (10m) HIGH TEMP RATED CABLE			
CSA RATED POWER CABLE: GAGE-LENGTH	AWG 12/4, 50' (15m) SEOOW			
SENSOR CABLE: ² GAGE-LENGTH	AWG 18/4, 33' (10m) HIGH TEMP RATED CABLE			
MOTOR PROTECTION	THERMAL SENSOR SWITCHES EMBEDDED IN EACH WINDING PHASE, 300°F (149°C)			
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE			
MAXIMUM LIQUID TEMPERATURE	200°F (93°C)			

1 - Available in other voltages for 50Hz

2 - Requires seal fail and thermal circuit in control panel for warranty validity.

3 - Continuous duty motor - see minimum submersion depth above.

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® JX15HSSF

Dwg:


DS-C09-002

Rev:

1

Date:

6/20/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

15HSSF - Dual Units

Frequency 60 Hz
Pump Speed 3450 RPM
Impeller 127mm

Specifications subject to change without notice