

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® SK55C		
	Dwg:	DS-C25-008	Rev:	2	Date:	8/25/2025

GENERAL DATA

MAX. FLOW:	611 GPM (2312.8 L/min)
MAX. HEAD:	51' (15.5m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	NON CLOG SHREDDER
MINIMUM SUBMERSION DEPTH: FOR CONT. DUTY ³	29.5" (749 mm)
SOLID SIZE:	3.5" (89 mm)
IMPELLER DIAMETER:	7.25" (184 mm)
DISCHARGE SIZE	4" NPT-FEMALE
SLIDE RAIL SYSTEM	4"
PUMP WEIGHT (without cable):	304 lbs (137.7 kg)
SHIPPING WEIGHT:	381 lbs (172.7 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/SILICON CARBIDE, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	304 SS
PUMP VOLUTE	CAST IRON
IMPELLER	DUCTILE IRON
IMPELLER SHREDDER BLADE	TUNGSTEN CARBIDE
LIP SEAL & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
BALL BEARING: PERM. LUBE. UPPER	6306
BALL BEARING: PERM. LUBE. LOWER	6309

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	7.5, SUBMERSIBLE , (CONTINUOUS DUTY ³)		
MOTOR RPM	1750		
MOTOR INSULATION CLASS	H		
MOTOR SERVICE FACTOR	1.10		
VOLTAGE - 60Hz ¹	230V	460V	575V
CURRENT F.L.A.	21	10.5	7.8
LOCKED ROTOR CURRENT (LRA)	130	65	48
POWER CABLE: GAGE-LENGTH	AWG 10/4, 33' (10m) SOOW		
SENSOR CABLE: ² GAGE-LENGTH	AWG 18/2, 33' (10m) STJ		
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD		
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE		
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)		

1 - Available in other voltages for 50Hz

2 - Requires a seal fail circuit in control panel for warning signal

3 - Continuous duty motor - see minimum submersion depth above

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® SK55

Dwg:




DS-C25-014

Rev:

1

Date:

6/20/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

55 - Dual Units

Frequency 60 Hz
Pump Speed 1750 RPM
Impeller 184mm

Specifications subject to change without notice