

INDUSTRIAL
FLOW
SOLUTIONS™**TECHNICAL DATA****BJM Pumps® SKX55CSS****Dwg:**

DS-C29-010

Rev:

2

Date:

8/29/2025

GENERAL DATA

MAX. FLOW:	611 GPM (2312.9 LPM)
MAX. HEAD:	51' (15.5m)
MAX. SUBMERSION DEPTH:	65' (20 m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE:	SOLIDS HANDLING, NON-CLOG SHREDDER
MINIMUM SUBMERSION DEPTH FOR CONT. DUTY ³ :	21" (533.4 mm)
SOLID SIZE:	3.5" (89 mm)
IMPELLER DIAMETER:	7.24" (184 mm)
DISCHARGE SIZE:	4" NPT-FEMALE
SLIDE RAIL SYSTEM	4" STAINLESS STEEL
PUMP WEIGHT (without cable):	321.9 lbs (146 kg)
SHIPPING WEIGHT:	399 lbs (181 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/SILICON CARBIDE, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	316 SS
PUMP VOLUTE	316 SS
SUCTION COVER	316 SS
IMPELLER	316 SS
IMPELLER SHREDDER BLADE	TUNGSTEN CARBIDE
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
BEARING, PERM. LUBRICATED, UPPER:	6306
BEARING, PERM. LUBRICATED, LOWER:	6309

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	7.5, SUBMERSIBLE, (CONTINUOUS DUTY ³)			
MOTOR RPM	1750			
MOTOR INSULATION CLASS	H			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 3PH - 60Hz ¹	208V	230V	460V	575V
CURRENT F.L.A.	23.1	21	10.5	7.8
LOCKED ROTOR CURRENT (LRA)	143	130	65	48
POWER CABLE: GAGE-LENGTH	AWG 10/4, 33' (10m) SOOW			
SENSOR CABLE: ² GAGE-LENGTH	AWG 18/2, 33' (10m) STJ			
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD			
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE			
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)			

1 - Available in other voltages for 50Hz

2 - Requires a seal fail circuit in control panel for warning signal.

3 - Continuous duty motor - see minimum submersion depth above.

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® SKX55CSS

Dwg:




DS-C29-016

Rev:

1

Date:

6/20/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

55CSS - Dual Units

Frequency 60 Hz
Pump Speed 1750 RPM
Impeller 184mm

Specifications subject to change without notice