

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® SKX150CSS		
	Dwg:	DS-C29-013	Rev:	2	Date:	8/29/2025

GENERAL DATA

MAX. FLOW:	874 GPM (3308.4 LPM)
MAX. HEAD:	105' (32m)
MAX. SUBMERSION DEPTH:	65' (20 m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE:	SOLIDS HANDLING, NON-CLOG SHREDDER
MINIMUM SUBMERSION DEPTH FOR CONT. DUTY ³ :	26" (660.4 mm)
SOLID SIZE:	3.5" (89 mm)
IMPELLER DIAMETER:	10.87" (276 mm)
DISCHARGE SIZE:	6" ANSI FLANGE
SLIDE RAIL SYSTEM	6" STAINLESS STEEL
PUMP WEIGHT (without cable):	535 lbs (242.7 kg)
SHIPPING WEIGHT:	630 lbs (285.8 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/SILICON CARBIDE, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	316 SS
PUMP VOLUTE	316 SS
SUCTION COVER	316 SS
IMPELLER	316 SS
IMPELLER SHREDDER BLADE	TUNGSTEN CARBIDE
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
BEARING, PERM. LUBRICATED, UPPER:	6306
BEARING, PERM. LUBRICATED, LOWER:	6309 (x2)

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	20, SUBMERSIBLE, (CONTINUOUS DUTY ³)	
MOTOR RPM	1750	
MOTOR INSULATION CLASS	H	
MOTOR SERVICE FACTOR	1.1	
VOLTAGE - 3PH - 60Hz ¹	460V	575V
CURRENT F.L.A.	25.7	19.8
LOCKED ROTOR CURRENT (LRA)	148	128
POWER CABLE: GAGE-LENGTH	AWG 8/4, 33' (10m) SOOW	
SENSOR CABLE: ² GAGE-LENGTH	AWG 18/2, 33' (10m) STJ	
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD	
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE	
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)	

1 - Available in other voltages for 50Hz

2 - Requires a seal fail circuit in control panel for warning signal.

3 - Continuous duty motor - see minimum submersion depth above.

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® SKX150CSS

Dwg:




DS-C29-015

Rev:

1

Date:

6/20/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

150CSS - Dual Units

Frequency
Pump Speed
Impeller

60 Hz
1750 RPM
276mm

Specifications subject to change without notice