



INDUSTRIAL
FLOW
SOLUTIONS™

TECHNICAL DATA

BJM Pumps® SKX22CSSF

Dwg:

DS-C30-020

Rev:

1

Date:

8/29/2025

GENERAL DATA

MAX. FLOW:	283 GPM (1071.3 LPM)
MAX. HEAD:	48' (14.6m)
MAX. SUBMERSION DEPTH:	65' (20 m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE:	SOLIDS HANDLING, NON-CLOG SHREDDER, HIGH TEMP
MINIMUM SUBMERSION DEPTH FOR CONT. DUTY ³ :	14" (355.6 mm)
SOLID SIZE:	1.6" (40.6 mm)
IMPELLER DIAMETER:	4.45" (113 mm)
DISCHARGE SIZE:	3" NPT-MALE
SLIDE RAIL SYSTEM	3" STAINLESS STEEL
PUMP WEIGHT (without cable):	113.3 lbs (51.4 kg)
SHIPPING WEIGHT:	132.3 lbs (60 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/SILICON CARBIDE, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	316 SS
PUMP VOLUTE	316 SS
SUCTION COVER	316 SS
IMPELLER	316 SS
IMPELLER SHREDDER BLADE	TUNGSTEN CARBIDE
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
BEARING, OIL LUBRICATED, UPPER:	6304
BEARING, OIL LUBRICATED, LOWER:	6305

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	3, SUBMERSIBLE OIL FILLED, (CONTINUOUS DUTY ³)			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	R, 428°F (220°C)			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 3PH - 60Hz ¹	208V	230V	460V	575V
CURRENT F.L.A.	9.45	9	4.5	3.2
LOCKED ROTOR CURRENT (LRA)	57	56	28	22
POWER CABLE: GAGE-LENGTH	AWG 10/4, 33' (10m) HIGH TEMP RATED CABLE			
SENSOR CABLE: ² GAGE-LENGTH	AWG 18/4, 33' (10m) HIGH TEMP RATED CABLE			
MOTOR PROTECTION	THERMAL SENSOR SWITCHES EMBEDDED IN EACH WINDING PHASE, 300°F (149°C)			
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE			
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)			

1 - Available in other voltages for 50Hz

2 - Requires seal fail and thermal circuit in control panel for warranty validity.

3 - Continuous duty motor - see minimum submersion depth above.

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® SKX22CSSF

Dwg:


DS-C30-010

Rev:

1

Date:

6/24/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

22CSSF - Dual Units

Frequency
Pump Speed
Impeller

60 Hz
3450 RPM
113mm

Specifications subject to change without notice