

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® SX22CSS		
	Dwg:	DS-C33-012	Rev:	1	Date:	8/13/2025

GENERAL DATA

MAX. FLOW:	260 GPM (984.2 L/min)
MAX. HEAD:	58' (17.6m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	OPEN VANE NON CLOG
MINIMUM SUBMERSION DEPTH: FOR CONT. DUTY ³	13.51" (343 mm)
SOLID SIZE:	1.6" (40.6 mm)
IMPELLER DIAMETER:	4.45" (113 mm)
DISCHARGE SIZE	3" NPT-MALE
SLIDE RAIL SYSTEM	3"
PUMP WEIGHT (without cable):	113 lbs (51.4 kg)
SHIPPING WEIGHT:	125 lbs (56.8 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/SILICON CARBIDE, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	316 SS
PUMP VOLUTE	316 SS
IMPELLER	316 SS
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
BALL BEARING: PERM. LUBE. UPPER	6304
BALL BEARING: PERM. LUBE. LOWER	6305

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	3, SUBMERSIBLE , (CONTINUOUS DUTY ³)			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	F			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 60Hz ¹	208V	230V	460V	575V
CURRENT F.L.A.	9.45	9	4.5	3.2
LOCKED ROTOR CURRENT (LRA)	57	56	28	22
POWER CABLE: GAGE-LENGTH	AWG 14/4, 33' (10m) STOW			
SENSOR CABLE: (OPTIONAL ²) GAGE-LENGTH	AWG 18/2, 33' (10m) SOOW			
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD			
SEAL LEAK DETECTOR (OPTIONAL ²)	Seal Minder® MOISTURE SENSING PROBE			
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)			

1 - Available in other voltages for 50Hz

2 - Requires a seal fail circuit in control panel for warning signal

3 - Continuous duty motor - see minimum submersion depth above

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA
(860) 631-3618 • www.flowsolutions.com

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps SX22CSS

Dwg:




DS-C33-007

Rev:

1

Date:

6/20/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

22CSS - Dual Units

Frequency
Pump Speed
Impeller

60 Hz
3450 RPM
113mm

Specifications subject to change without notice