



INDUSTRIAL
FLOW
SOLUTIONS™

TECHNICAL DATA

BJM Pumps® J37HF

Dwg:

DS-C05-005

Rev:

2

Date:

9/3/2025

GENERAL DATA

APPROVALS:	CSA APPROVAL (AVAILABLE UPON REQUEST)	
MAX. FLOW:	190 GPM (719.2 LPM)	
MAX. HEAD:	116' (35.4m)	
MAX. SUBMERSION DEPTH:	65' (20 m) or limited to length of power cord, Consult factory for deeper depths	
PUMP TYPE:	DEWATERING, SIDE DISCHARGE, HIGH TEMP	
MINIMUM SUBMERSION DEPTH FOR CONT. DUTY ³ :	12" (304.8 mm)	
PUMP DOWN WATER LEVEL:	6.25" (158.75 mm)	
SOLID SIZE:	0.37" (9.5 mm)	
STRAINER OPENING:	0.37" (9.5 mm)	
IMPELLER DIAMETER:	5.8" (147 mm)	
DISCHARGE SIZE:	2" NPT-MALE	
SLIDE RAIL SYSTEM	2" CAST IRON	
PUMP WEIGHT (without cable):	97 lbs (44 kg)	
SHIPPING WEIGHT:	108 lbs (49 kg)	

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR CASING	304 SS
IMPELLER & VOLUTE	CAST IRON
STRAINER	STEEL
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
BEARING, OIL LUBRICATED, UPPER:	6304
BEARING, OIL LUBRICATED, LOWER:	6305

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	5, SUBMERSIBLE OIL FILLED, (CONTINUOUS DUTY ³)			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	R, 428°F (220°C)			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 3PH - 60Hz ¹	208V	230V	460V	575V
CURRENT F.L.A.	14.7	14	7	5.5
LOCKED ROTOR CURRENT (LRA)	86.5	85	43	38
STANDARD POWER CABLE: GAGE-LENGTH	AWG 10/4, 33' (10m) HIGH TEMP RATED CABLE			
CSA RATED POWER CABLE: GAGE-LENGTH	AWG 6/4, 50' (15m) SEOOW		AWG 10/4, 50' (15m) SEOOW	
SENSOR CABLE: ² GAGE-LENGTH	AWG 18/4, 33' (10m) HIGH TEMP RATED CABLE			
MOTOR PROTECTION	THERMAL SENSOR SWITCHES EMBEDDED IN EACH WINDING PHASE, 300°F (149°C)			
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE			
MAXIMUM LIQUID TEMPERATURE	200°F (93°C)			

1 - Available in other voltages for 50Hz

2 - Requires seal fail and thermal circuit in control panel for warranty validity.

3 - Continuous duty motor - see minimum submersion depth above.

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® J37HF

Dwg:




DS-C05-004

Rev:

2

Date:

7/23/2025



Flow

Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

37HF - Dual Units

Frequency
Pump Speed
Impeller

60 Hz
3450 RPM
135mm

Specifications subject to change without notice