

**TECHNICAL DATA**  
**MODEL J37H-F**  
**BJM Pumps® SUBMERSIBLE PUMP-CAST IRON**  
**For High Temperature Service**  
**GENERAL DATA**

MAX. FLOW: GPM (L/min)	192 GPM (726 L/min)
MAX. HEAD: ft (m)	113' (34.4 m)
MAX. SUBMERSION DEPTH: ft (m)	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	SUMP, HIGH TEMPERATURE
MINIMUM SUBMERSION DEPTH: in(mm)	12" (305 mm)
SOLID SIZE: in (mm)	3/8" (9.5 mm)
STRAINER OPENING	0.375" (9.5 mm) diameter
IMPELLER DIAMETER: in (mm)	5.8" (147 mm)
DISCHARGE SIZE	2" NPT-MALE
PUMP WEIGHT, without cable: lbs (kg)	97 lbs (44.1 kg)
SHIPPING WEIGHT: lbs (kg)	108 lbs (49 kg)

**CONSTRUCTION/MATERIAL DATA**

MECHANICAL SEAL - UPPER	CARBON/CERAMIC – VITON® FITTED
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE – VITON FITTED
MOTOR CASING	304 SS
PUMP VOLUTE	CAST IRON
IMPELLER- MULTI VANE	CAST IRON
STRAINER	STEEL
LIPSEAL & O-RINGS	VITON
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
QTY. OIL IN MOTOR STATOR	60 U.S. FL. OZ. (1774 C.C.), OIL-FILLED W/ SHELL FM 32, NSF APPROVED
QTY. OIL IN SEAL CHAMBER	10.8 U.S. FL. OZ. (320 C.C.), SHELL FM 32, NSF APPROVED
BALL BEARING: OIL LUBRICATED UPPER	6304
BALL BEARING: OIL LUBRICATED LOWER	6305

**ELECTRICAL /MOTOR DATA**

MOTOR: TYPE, RATING HP	Submersible, Oil-Filled , Continuous Duty, 5			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	R, 428°F (220°C)			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 3 PH, 60 Hz	208V option	230V	460V	575V option
CURRENT F.L.A.	14.7	14	7	5.5
LOCKED ROTOR CURRENT (LRA)	86.5	85	43	38
MOTOR PROTECTION	THERMAL SENSOR SWITCHES EMBEDDED IN EACH WINDING PHASE, 300°F (149°C)			
POWER CORD: GAGE; LENGTH	A.W.G. 10/4; 33' (10 m), HIGH TEMP. RATED CORD			
SENSOR CABLE: GAGE; LENGTH	A.W.G. 18/4; 33' (10 m), HIGH TEMP. RATED CABLE			
MAXIMUM LIQUID TEMPERATURE	200°F (93°C)			
SEAL LEAK DETECTOR <sup>1</sup>	Seal Minder®; MOISTURE SENSING PROBE			

1- Requires a seal fail circuit in control panel for warning signal.

©2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive

New Haven, CT. 06513, USA

Tel: (860)399-5937 - Fax: (860)399-7784


REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Viton® is a registered trademark of DuPont Performance Elastomers.

Seal Minder® is a registered trademark of Industrial Flow Solutions Operating, LLC. All rights reserved.

### MODEL: J37H-F



3/26/2020

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE