

TECHNICAL DATA
MODEL JX55CSS
BJM Pumps® SUBMERSIBLE PUMP - 316 SS
GENERAL DATA

MAX. FLOW: GPM (L/min)	515 GPM (1949 L/min)
MAX. HEAD: ft (m)	91' (27.7 m)
MAX. SUBMERSION DEPTH: ft (m)	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	SUMP, SIDE DISCHARGE
MINIMUM SUBMERSION DEPTH: in(mm)	16" (407 mm)
SOLID SIZE: in (mm)	3/8" (9.5 mm)
STRAINER OPENING	0.375" (9.5 mm) diameter
IMPELLER DIAMETER: in (mm)	5.39" (137 mm)
DISCHARGE SIZE	4" NPT FEMALE
SLIDE RAIL SYSTEM	4"
PUMP WEIGHT, without cable: lbs (kg)	190 lbs (86.4 kg)
SHIPPING WEIGHT: lbs (kg)	233 lbs (106 kg)

CONSTRUCTION / MATERIAL DATA

MECHANICAL SEAL - UPPER	CARBON/CERAMIC
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE
MOTOR CASING	316 SS
PUMP VOLUTE	316 SS
IMPELLER- MULTI VANE	316 SS
STRAINER	316 SS
LIPSEAL & O-RINGS	VITON
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
QTY. OIL IN SEAL CHAMBER	45.6 U.S. FL. OZ. (1350 C.C.)
BALL BEARING: PERM. LUBE. UPPER	6305
BALL BEARING: PERM. LUBE. LOWER	6207 (x2)

ELECTRICAL / MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 7.5 (CONTINUOUS DUTY ³)			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	H			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE ¹ - 3 PH, 60 Hz	208V option	230V	460V	575V option
CURRENT F.L.A.	23.1	21	10.5	7.6
LOCKED ROTOR CURRENT (LRA)	138.6	126	63	47
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD			
POWER CORD: GAGE; LENGTH	A.W.G. 10/4; 33' (10 m), SOOW			
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)			
SEAL LEAK DETECTOR ² (OPTIONAL)	Seal Minder®; MOISTURE SENSING PROBE			

1- Available in other voltages (and in 50 Hz).

2- Requires a seal fail circuit in control panel for warning signal.

3 - NOTE: STAINLESS STEEL PUMPS **MAY NOT BE SUITABLE** FOR CONTINUOUS DUTY IN ALL APPLICATIONS. PLEASE CONSULT WITH BJM PUMPS. MAY BE NECESSARY TO OFFER 'F' SERIES HIGH TEMPERATURE PUMPS WHEN CONSIDERING CONTINUOUS DUTY OPERATION.


©2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive
 New Haven, CT. 06513, USA

Tel: (860)399-5937 - Fax: (860)399-7784



MODEL: JX55CSS



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE