

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® KZN220LR		
	Dwg:	DS-C17-020	Rev:	1	Date:	8/20/2025

GENERAL DATA

MAX. FLOW:	1691 GPM (6401.1 L/min)
MAX. HEAD:	77' (23.7m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	SLURRY HANDLING TOP DISCHARGE
MINIMUM SUBMERSION DEPTH: FOR CONT. DUTY ³	53" (1326 mm)
PUMP DOWN WATER LEVEL:	16" (406 mm)
SOLID SIZE:	1.5" (38.1 mm)
STRAINER OPENING:	1.38" (34.9 mm)
IMPELLER DIAMETER:	10.24" (260 mm)
DISCHARGE SIZE	6" NPT-MALE (8" FLANGE OPTIONAL)
PUMP WEIGHT (without cable):	1152 lbs (522.7 kg)
SHIPPING WEIGHT:	1284 lbs (582.3 kg)

CONSTRUCTION / MATERIAL DATA

DUAL MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	CAST IRON
PUMP VOLUTE	DUCTILE IRON WITH INTERIOR HARDNESS COATING TO 1180 DPH(Rc 71)
WEAR PLATE	HI-CHROME
AGITATOR	HI-CHROME
IMPELLER	HI-CHROME
STRAINER/STAND	STEEL
LIP SEAL & O-RINGS	BUNA-N
ROTOR SHAFT	410 SS
EXTERNAL HARDWARE	304 SS
BALL BEARING: PERM. LUBE. UPPER	6309
BALL BEARING: PERM. LUBE. LOWER	6314 X2

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	30, SUBMERSIBLE , (CONTINUOUS DUTY ³)	
MOTOR RPM	1750	
MOTOR INSULATION CLASS	H	
MOTOR SERVICE FACTOR	1.15	
VOLTAGE - 60Hz ¹	460V	575V
CURRENT F.L.A.	39	30.2
LOCKED ROTOR CURRENT (LRA)	230	184
POWER CABLE: GAGE-LENGTH	AWG 4/5, 50' (15m) SOOW	
SENSOR CABLE: (OPTIONAL ²) GAGE-LENGTH	AWG 18/2, 50' (15m) SOOW	
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD	
SEAL LEAK DETECTOR (OPTIONAL ²)	Seal Minder® MOISTURE SENSING PROBE	
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)	

1 - Available in other voltages for 50Hz

2 - Requires a seal fail circuit in control panel for warning signal

3 - Continuous duty motor - see minimum submersion depth above

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® KZN220LR

Dwg:




DS-C17-009

Rev:

1

Date:

6/12/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

220LR - Dual Units

Frequency 60 Hz
Pump Speed 1750 RPM
Impeller 260mm

Specifications subject to change without notice