

MODEL KZN-HYD3

3" HYDRAULIC SUBMERSIBLE SLURRY PUMP with AGITATOR

1. Built-in agitator to lift solids into suspension
2. Wear resistant chrome iron impeller, agitator and wear plate
3. Variable speed hydraulic motor drive
4. Top discharge allows pump to fit through a 17 inch opening
5. Wide range performance curve allows use of hydraulic flows up to 8.2 GPM to suit application
6. Safe hydraulic drive: use where electric power is hazardous, impractical or unavailable
7. Run dry with no damage
8. Oil lubricated double silicon carbide seals

GENERAL DATA

MAX. FLOW: GPM (L/min)	367 GPM (1391 L/min)
MAX. HEAD: ft (m)	53.5' (16.3 m)
DISCHARGE SIZE	3" NPT-MALE
PUMP DOWN WATER LEVEL: in (mm)	12" (305 mm)
SOLID SIZE	0.875" (22.2 mm)
STRAINER OPENING	1.375" (34.9 mm)
HEIGHT	30 1/4" (77 cm)
DIAMETER (@ widest point)	16 1/4" (41 cm)
WEIGHT	231 lbs. (105 kg)

CONSTRUCTION/MATERIAL DATA

DUAL MECHANICAL SEALS	SILICON CARBIDE/SILICON CARBIDE
MOTOR HOUSING	CAST IRON
PUMP VOLUTE	DUCTILE IRON
WEAR PLATE	HI-CHROME IRON
AGITATOR	HI-CHROME IRON
IMPELLER	MULTI VANE, HI-CHROME IRON
LIP SEALS & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
QTY. OIL IN SEAL CHAMBER	49 U.S. FL. OZ. (1450 C.C.)
BALL BEARING: PERM. LUBE. UPPER	6306
BALL BEARING: PERM. LUBE. LOWER	6308

HYDRAULIC DATA

HOSE PORTS	1/2" and 3/4" NPT(F)
HYDRAULIC OIL	214-320 s.s.u. @ 100 °F (64 °C)
INPUT FLOW	Max. 8.2 GPM (31 LPM)
OPERATING PRESSURE	Max. 2200 PSI (149.6 Bar)
POWER SOURCE	Any Open Center Hydraulic System

© 2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive
New Haven, CT. 06513, USA
Tel: (860)399-5937 - Fax: (860)399-7784

MODEL: KZN-HYD3 Performance curves

Curves are based on pumping water at 60 deg. F. Consult factory for performance curves other than shown below.

