



TECHNICAL DATA
MODEL LWAE37
LIGHT WEIGHT AGITATOR DEWATERING PUMP—CHROME IRON / DUCTILE IRON

GENERAL DATA

MAX. FLOW: GPM (L/min)	245 GPM (927 L/min)
MAX. HEAD: ft (m)	92' (28 m)
PUMP TYPE	TOP DISCHARGE, DEWATERING, AGITATOR
SOLID SIZE: in (mm)	0.4" (11 mm)
MAX. SUBMERSION DEPTH: ft (m)	65' (20m) or limited to length of power cord, Consult factory for deeper depths
MIN. SUBMERSION DEPTH: ft (m)	7.6" (194 mm)
DISCHARGE SIZE	3" NPT
PUMP WEIGHT, without cable: lbs (kg)	106 lbs. (48 kg)
SHIP WEIGHT: lbs (kg)	146 lbs. (66 kg)

CONSTRUCTION / MATERIAL DATA

MECHANICAL SEAL - UPPER	CARBON/CERAMIC
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE
MOTOR HOUSING	304 SS
PUMP VOLUTE	ASTM A48 CLASS 30 CAST IRON
SUCTION COVER	CAST IRON, 223 BHN
WEAR PLATE	HIGH CHROME, 653 BHN
AGITATOR	HARDENED DUCTILE IRON, 477 BHN
IMPELLER	HIGH CHROME, 653 BHN
STRAINER/STAND	STEEL
LIP SEALS & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS

ELECTRICAL / MOTOR DATA


MOTOR: TYPE, RATING HP	SUBMERSIBLE, 5 (CONTINUOUS DUTY)		
MOTOR RPM	3450		
MOTOR INSULATION CLASS	F		
MOTOR SERVICE FACTOR	1.15		
VOLTAGE - 3 PH, 60 Hz	230V	460V	575V
CURRENT F.L.A.	13.8	6.9	5.5
MOTOR PROTECTION	OVERLOAD REQUIRED IN CONTROL		
POWER CORD: GAGE; LENGTH; TYPE	A.W.G. 12/5; 50' (15 m); SOOW(EPR JACKET)		
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)		

©2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive
 New Haven, CT. 06513, USA
 Tel: (860)399-5937 - Fax: (860)399-7784

REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
 LWA® is a registered trademark of Industrial Flow Solutions Operating, LLC. All rights reserved.

MODEL: LWAE37



3/30/2020

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE