

**TECHNICAL DATA MODEL TIGF 32-9NL
 BJM Pumps® SUBMERSIBLE PUMP**

GENERAL DATA

MAX. FLOW: GPM (L/min)	46 GPM (174 L/min)
MAX. HEAD: ft (m)	27' (8.2 m)
MAX. SUBMERSION DEPTH: ft (m)	33' (10 m) or limited to length of power cord
PUMP TYPE	TOP or SIDE DISCHARGE, CHEMICAL RESISTANT
STRAINER OPENING	0.25" (6.35 mm)
PUMP DOWN WATER LEVEL: in (mm)	1.5" (38 mm)
IMPELLER DIAMETER: in (mm)	3.15" (80 mm)
DISCHARGE CONNECTION	1 ¼" NPT-FEMALE or 1 ½" TAPERED HOSE
PUMP NET WEIGHT: lbs (kg)	13.5 lbs (6.2 kg)
SHIPPING WEIGHT: lbs (kg)	17 lbs (7.7 kg)

CONSTRUCTION/MATERIAL DATA

LIP SEAL - UPPER	FKM (fluoroelastomer)
LIP SEAL - LOWER	FKM (fluoroelastomer)
O-RINGS	FKM (fluoroelastomer)
O-RINGS - MOTOR HOUSING	FKM (fluoroelastomer)
PUMP TOP COVER	Ultramid B3 WG 7
PUMP HANDLE	PP (Polypropylene)
PUMP CASING	NORYL GTX830 with 30% glass reinforcement
IMPELLER – MULTI VANE	NORYL GTX830
SUCTION COVER PLATE	NORYL GTX830
STRAINER	PPO-PA (Polyphenylene Oxide)
ROTOR SHAFT	TITANIUM
EXTERNAL HARDWARE	TITANIUM
QTY. OIL IN MOTOR	15 U.S. FL. OZ. (443 C.C.)
BALL BEARING: PERM. LUBE. UPPER	6001
BALL BEARING: PERM. LUBE. LOWER	6002

ELECTRICAL /MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 0.4
MOTOR RPM	3450
MOTOR INSULATION CLASS	F
MOTOR SERVICE FACTOR	1.1
VOLTAGE ¹	115, 1 PH, 60 Hz
CURRENT F.L.A.	5
MOTOR PROTECTION	THERMAL BREAKER, 150°C (302°F)
POWER CORD: GAGE; LENGTH	A.W.G. 16/3; 15' (4.5m), EPDM
MINIMUM SUBMERSION DEPTH FOR CONTINUOUS DUTY: in (mm)	3.5" (89 mm)
MAXIMUM LIQUID TEMPERATURE	135°F (57°C) - Continuous duty 195°F (90°C) - Intermittent use submerge less than 20 minutes
LEVEL CONTROL FLOAT SWITCH	NOT AVAILABLE

1- Available in other voltages (and in 50 Hz).


©2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive

New Haven, CT. 06513, USA

Tel: (860)399-5937 - Fax: (860)399-7784

PERFECTA® SERIES



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE