

**TECHNICAL DATA**  
**MODEL SK08C-F**  
**BJM Pumps@SHREDDER PUMP-CAST IRON**  
**For High Temperature Service GENERAL**  
**DATA**

MAX. FLOW: GPM (L/min)	95 GPM (359 L/min)
MAX. HEAD: ft (m)	48' (14.6 m)
MAX. SUBMERSION DEPTH: ft (m)	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	NON CLOG SHREDDER
SOLID SIZE: in (mm)	2" (50 mm)
IMPELLER DIAMETER: in (mm)	4.33" (110 mm)
DISCHARGE SIZE	2" NPT-MALE
SLIDE RAIL DISCHARGE SIZE	2"
PUMP WEIGHT, without cable: lbs (kg)	58 lbs (26.4 kg)
SHIPPING WEIGHT: lbs (kg)	68 lbs (31 kg)

**CONSTRUCTION/MATERIAL DATA**

MECHANICAL SEAL - UPPER	CARBON/ SILICON CARBIDE , FKM
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE, FKM
MOTOR HOUSING	304 SS
PUMP VOLUTE	CAST IRON
IMPELLER	SINGLE VANE, HIGH-CHROME
IMPELLER SHREDDER BLADE	TUNGSTEN CARBIDE
STAND	CAST IRON
SUCTION COVER	HIGH-CHROME
LIPSEAL & O-RINGS	FKM
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
QTY. OIL IN MOTOR STATOR	32 U.S. FL. OZ. (946 C.C.), OIL-FILLED W/ SHELL FM 32, NSF APPROVED
QTY. OIL IN SEAL CHAMBER	7.8 U.S. FL. OZ. (230 C.C.), SHELL FM 32, NSF APPROVED
BALL BEARING: OIL LUBRICATED UPPER	6203
BALL BEARING: OIL LUBRICATED LOWER	6304

**ELECTRICAL /MOTOR DATA**

MOTOR: TYPE, RATING HP	Submersible, Oil-Filled , Continuous Duty, 1			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	R, 428°F (220°C)			
MOTOR SERVICE FACTOR	1.1			
VOLTAGE - 3 PH, 60 Hz	208V option	230V	460V	575V option
CURRENT F.L.A.	3.5	3.2	1.6	1.3
LOCKED ROTOR CURRENT (LRA)	18.15	18	9	8
MOTOR PROTECTION	THERMAL SENSOR SWITCHES EMBEDDED IN EACH WINDING PHASE, 300°F (149°C)			
POWER CORD: GAGE; LENGTH	A.W.G. 16/4; 33' (10m), HIGH TEMP. RATED CORD			
SENSOR CABLE: GAGE; LENGTH	A.W.G. 18/4; 33' (10 m), HIGH TEMP. RATED CABLE			
MAXIMUM LIQUID TEMPERATURE	200°F (93°C)			
SEAL LEAK DETECTOR <sup>1</sup>	Seal Minder®; MOISTURE SENSING PROBE			

1- Requires a seal fail circuit in control panel for warning signal.


©2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive  
 New Haven, CT. 0613, USA  
 Tel: (860)399-5937 - Fax: (860)399-7784

REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE  
 Seal Minder® is a registered trademark of Industrial Flow Solutions Operating, LLC. All rights reserved.



# BJM Pumps MODEL: SK08C-F



4/9/2020

FLOW RATE PER MINUTE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE