



INDUSTRIAL
FLOW
SOLUTIONS™

TECHNICAL DATA

BJM Pumps® XP-SKG22C

Dwg:

DS-C39-004

Rev:

2

Date:

8/14/2025

GENERAL DATA

APPROVALS:	EXPLOSION PROOF FM APPROVED CLASS1, DIVISION 1, GROUP C & D	
MAX. FLOW:	276 GPM (1044.7 L/min)	
MAX. HEAD:	42' (12.8m)	
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths	
PUMP TYPE	AXIAL & RADIAL SHREDDER	
MINIMUM SUBMERSION DEPTH: FOR CONT. DUTY ¹	26.4" (670 mm)	
IMPELLER DIAMETER:	6.5" (165 mm)	
DISCHARGE SIZE	3" NPT-FEMALE	
SLIDE RAIL SYSTEM	3" Non-Sparking	
PUMP WEIGHT (without cable):	198 lbs (90 kg)	
SHIPPING WEIGHT:	236 lbs (107 kg)	

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC, BUNA-N
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, BUNA-N
MOTOR HOUSING	304 SS
PUMP VOLUTE	CAST IRON
SUCTION COVER	HI-CHROME
IMPELLER	HI-CHROME
CUTTER COMPONENTS	440C SS
STAND	CAST IRON
LIP SEAL & O-RINGS	BUNA-N
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	304 SS
BALL BEARING: PERM. LUBE. UPPER	6304
BALL BEARING: PERM. LUBE. LOWER	6307

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	3, SUBMERSIBLE , (CONTINUOUS DUTY ¹)			
MOTOR RPM	1750			
MOTOR INSULATION CLASS	F			
MOTOR SERVICE FACTOR	1.15			
VOLTAGE - 60Hz	208V	230V	460V	575V
CURRENT F.L.A.	9.4	8.9	4.5	3.6
LOCKED ROTOR CURRENT (LRA)	51	48.3	24.4	19.5
POWER CABLE: GAGE-LENGTH	AWG 14/4, 50' (15m) SOOW			
SENSOR CABLE: ² GAGE-LENGTH	AWG 14/4, 50' (15m) SOOW			
MOTOR PROTECTION	TWO NORMALLY CLOSED THERMOSTATS			
SEAL LEAK DETECTOR ²	Seal Minder® MOISTURE SENSING PROBE			
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)			

1 - Continuous duty motor - see minimum submersion depth above

2 - Seal fail and thermal sensor circuit must be properly connected for warranty validity

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps XP-SKG22C

Dwg:




DS-C39-007

Rev:

1

Date:

6/20/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

22C - Dual Units

Frequency 60 Hz
Pump Speed 1750 RPM
Impeller 165.1mm

Specifications subject to change without notice