

INDUSTRIAL
FLOW
SOLUTIONS™**TECHNICAL DATA****BJM Pumps® GRIX 32-2-110****Dwg:**

DS-C57-006

Rev:

1

Date:

11/8/2023

GENERAL DATA

MAX. FLOW:	37 GPM (140.1 L/min)
MAX. HEAD:	108' (32.9m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	GRINDER PUMP
MINIMUM SUBMERSION DEPTH:	17" (421 mm)
IMPELLER DIAMETER:	5.32" (135 mm)
DISCHARGE SIZE	1.25" NPS FEMALE & DN32 PN6 FLANGE
PUMP WEIGHT, without cable:	56.2 lbs (25.5 kg)
SHIPPING WEIGHT:	57.3 lbs (26 kg)

CONSTRUCTION / MATERIAL DATA

MECHANICAL SEAL	SILICON CARBIDE/CERAMIC FKM
MOTOR CASING	CAST IRON, EN 1561 EN-GJL-200
PUMP VOLUTE	CAST IRON, EN 1561 EN-GJL-200
IMPELLER	CAST IRON, EN 1561 EN-GJL-200
LIPSEAL & O-RINGS	FKM
ROTOR SHAFT	STAINLESS STEEL AISI 420
EXTERNAL HARDWARE	STAINLESS STEEL A2-70
OIL IN SEAL CHAMBER: TYPE; QTY.	Q8 WF15; 18.2 U.S. FL. OZ. (537 C.C.)
UPPER BALL BEARING: PERM. LUBE.	6202-2Z
LOWER BALL BEARING: PERM. LUBE.	6302-2Z

ELECTRICAL / MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 1.5 (CONTINUOUS DUTY ²)	
MOTOR RPM	3450	
MOTOR INSULATION CLASS	F	
MOTOR SERVICE FACTOR	1.1	
PHASE	THREE	
VOLTAGE ¹ - 60 Hz	230V	460V
CURRENT F.L.A.	5	2.5
LOCKED ROTOR CURRENT (LRA)	25.9	13
POWER CORD: GAGE; LENGTH	A.W.G. 16/4; 33' (10 m), STOW	
MOTOR PROTECTION	IP 68, OVERLOAD REQUIRED IN CONTROL	
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)	

1 - Available in other voltages for 50Hz

2 - Continuous duty motor - see minimum submersion depth above

©2023 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA
(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL FLOW SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® GRIX 32-2-110

Dwg:




DS-C57-002

Rev:

1

Date:

11/8/2023



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

32-2-110 - Dual Units

Frequency	60 Hz
Pump Speed	3450 RPM
Impeller	135mm

Specifications subject to change without notice