

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® H2-56		
	Dwg:	DS-C59-015	Rev:	2	Date:	9/9/2024

GENERAL DATA

MAX. FLOW:	176 GPM (666.2 L/min)
MAX. HEAD:	126' (38.4m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	HIGH HEAD DEWATERING
MINIMUM SUBMERSION DEPTH:	25" (610 mm)
SOLID SIZE:	0.4" (10 mm)
IMPELLER DIAMETER:	5.63" (143 mm)
DISCHARGE SIZE	DN65 PN6
PUMP WEIGHT, without cable:	176.4 lbs (80 kg)
SHIPPING WEIGHT:	187.4 lbs (85 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/SILICON CARBIDE FKM
MOTOR CASING	CAST IRON, EN 1561
PUMP VOLUTE	CAST IRON, EN 1561
IMPELLER	CAST IRON, EN 1561
O-RINGS	BUNA
ROTOR SHAFT	STAINLESS STEEL AISI 420
EXTERNAL HARDWARE	STAINLESS STEEL A2-70
BALL BEARING: PERM. LUBE. UPPER	6206-ZZCMDNS7S6
BALL BEARING: PERM. LUBE. LOWER	3306B-2ZRTNG

ELECTRICAL / MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 7.5 (CONTINUOUS DUTY ²)
MOTOR RPM	3450
MOTOR INSULATION CLASS	F
MOTOR SERVICE FACTOR	1.1
VOLTAGE ¹ - 60 Hz	460V
CURRENT F.L.A.	11
LOCKED ROTOR CURRENT (LRA)	59.8
POWER CORD: GAGE; LENGTH	AWG 12/4 + 16/3, 33' (10m), SOOW
MOTOR PROTECTION	THERMAL OVERLOAD
SEAL LEAK DETECTOR ³	Seal Minder® MOISTURE SENSING PROBE
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)

1 - Available in other voltages for 50Hz

2 - Continuous duty motor - see minimum submersion depth above

3 - Requires a seal fail circuit in control panel for warning signal

©2024 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA
(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® H2-56

Dwg:




DS-C59-014

Rev:

1

Date:

3/22/2024



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

56 - Dual Units

Frequency 60 Hz
Pump Speed 3450 RPM
Impeller 143mm

Specifications subject to change without notice