



INDUSTRIAL
FLOW
SOLUTIONS™

TECHNICAL DATA

BJM Pumps® V4-22

Dwg:

DS-C62-011

Rev:

1

Date:

5/28/2024

GENERAL DATA

MAX. FLOW:	348 GPM (1317.3 L/min)
MAX. HEAD:	33' (10.1m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	NON-CLOG VORTEX
MINIMUM SUBMERSION DEPTH:	25" (613 mm)
SOLID SIZE:	3.2" (80 mm)
IMPELLER DIAMETER:	6.15" (156 mm)
DISCHARGE SIZE	DN80 PN16
PUMP WEIGHT, without cable:	145.5 lbs (66 kg)
SHIPPING WEIGHT:	149.6 lbs (67.86 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/SILICON CARBIDE FKM
MOTOR CASING	CAST IRON, EN 1561
PUMP VOLUTE	CAST IRON, EN 1561
IMPELLER	CAST IRON, EN 1561
O-RINGS	BUNA
ROTOR SHAFT	STAINLESS STEEL AISI 420
EXTERNAL HARDWARE	STAINLESS STEEL A2-70
BALL BEARING: PERM. LUBE. UPPER	6205-ZZCMDNS7S6
BALL BEARING: PERM. LUBE. LOWER	3205B-2ZRTNG

ELECTRICAL / MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 3 (CONTINUOUS DUTY ²)
MOTOR RPM	1750
MOTOR INSULATION CLASS	F
MOTOR SERVICE FACTOR	1.1
VOLTAGE ¹ - 60 Hz	460V
CURRENT F.L.A.	4.8
LOCKED ROTOR CURRENT (LRA)	18.7
POWER CORD: GAGE; LENGTH	AWG 16/7, 33' (10m), SOOW
MOTOR PROTECTION	THERMAL OVERLOAD
SEAL LEAK DETECTOR ³	Seal Minder® MOISTURE SENSING PROBE
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)

1 - Available in other voltages for 50Hz

2 - Continuous duty motor - see minimum submersion depth above

3 - Requires a seal fail circuit in control panel for warning signal

©2024 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA
(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® V4-22

Dwg:




DS-C62-005

Rev:

1

Date:

5/21/2024



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

22 - Dual Units

Frequency 60 Hz
Pump Speed 1750 RPM
Impeller 156mm

Specifications subject to change without notice